


Composed of 100% polypropylene meltblown, Pro-Wipe OS is engineered for oil absorption and retention. Surfactant free and low linting, this wiper is also ideal for use in applications where cleanliness is vital in the manufacturing environment.



Key Attributes

- 100% polypropylene
- Meltblown nonwoven
- High loft and soft texture
- No binders, surfactants or other chemical additives
- Specifically designed to absorb oil and repel water
- Low linting

Benefits

- Engineered for oil absorption and retention
- Very low particle and fiber generation
- Autoclavable
- Excellent resistance to acids and bases
- Surfactant free and extremely low non-volatile residues

Applications

- Oil absorbent low particle and fiber work surface material
- Designed for removal of etchants, acids, and other chemical spills
- Removes and retains oil and hydrocarbon based fluids
- Ideal for tray lining and other lab applications
- Excellent for use in capsule drying and polishing
- FDA 21 CFR - Food contact compliant

Pro-Wipe® Family

Pro-Wipe® AP
Pro-Wipe® OS
Pro-Wipe® SE Knit



Flat Pack

Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m ²	79.6	TAPPI T410
Fibers	≥ 100µm	fibers/	0.88	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2
Oil Absorbency		%	623	Berkshire Procedure QA-1041
Extractable Matter	DI Water	%	0.0020	IEST-RP.CC004.3, Sec 7.1.2
	IPA	%	0.020	
Tensile Strength	MD	lb/in	9.9	ASTM D5035
	CD	lb/in	7.4	

Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	Style
Pro-Wipe® OS	PWOS12.12	12x12" (30x30cm)	100	12	Flat packed

Contact: Tel 44 (0) 870 757 2877 inquiries@berkshire.uk.com

